

Electrical Properties

- 1.100% Test(Open Short Miss Wire)
- 2.Contact Resistance: 3Ω Maximum
- 3.Insulation Resistance: 5MΩ Minimum
- 4.Hi-Pot: 300V 10ms

P1	Drain	P2
4	Black	1
2	White	10
1	Red	6
△ PIN OUT		

ITEM	PARTS NAME	SPECIFICATION	STANDARD	Q'TY	REMARK		
7	H.S. TUBE	∅5.0mm L=20mm	Color:Black	2PCS	.		
6	H.S. TUBE	∅0.8mm L=20mm	Color:Black	2PCS	.		
5	CABLE	UL2464 28AWGx3C+AEB	OD=3.5mm	Color:Black	1PCS	.	
4	TERMINAL	2.54mm Copper, Tin Plated	PVK-T-22	3PCS	.		
3	HOUSING	2.54mm 2x5Pin Thermoplastic	Color:Black PVK-H-2X05	1PCS	.		
2	TERMINAL	1.25mm Phosphor Bronze, Tin Plated	FH-T-28	3PCS	.		
1	HOUSING	1.25mm 4Pin Nylon66	UL94V-0	Color:White	FH-H-04	1PCS	.

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X. ±  
.X ± 0.35  
.XX ± 0.25  
.XXX ± 0.15  
ANG ±

PPOJECTION



ORDER INFORMATION

FHPVK-04B050328R1-Fxxx-LF

SERIES

LEADFREE

37C:370mm

43C:430mm

FEMALE TO FEMALE

ROUND CABLE

04 TO 10P3C WAY

DESCRIPTION: Cable 1.25mm 4Pin To 2.54mm 2x5Pin UL2464#28x3C+AEB L=430mm OD:3.8 Black