

**SPECIFICATION**

**MATERIAL**

Insulator: Polyester resin and glass fiber reinforced (UL 94V-0)

Contacts: Phosphor bronze

**CONTACT PLATING**

Underplate: 50u" Nickel

Contact area: 1u"~30u" Selective Gold

Solder tails area: 100u" Tin/Lead

**ELECTRICAL**

Operation voltage: 250 VAC max.

Current rating: 3 Amps max.

Contact resistance: 15 mohms max.

Insulation resistance: 3000 Mohms min @ 500 VDC

Dielectric withstanding voltage: 1000 VAC / minute

Operating temperature: -55°C TO +105°C

POSITION	A	B	C	D
DFM-S-09	16.30	25.00	30.8	22.4

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ± 0.10  
ANG ±

PPOJECTION



**ORDER INFORMATION**

DFM-S-09-LF  
SERIES | LEADFREE  
09 WAY  
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: