



PCB LAYOUT
TOP VIEW

CAT. NO.	PIN	SCHEMATIC
DCJ-RLT-20	∅2.0	
DCJ-RLT-25	∅2.5	

LTR	PART NAME	QTY	MATERIAL	REMARK
6	TERMINAL	1	C2680 t=0.5	Sn PLATED
5	SHUNT TERMINAL	1	C2680 t=0.45	Sn PLATED
4	TIP TERMINAL	1	C5191 t=0.3	Sn PLATED
3	PIN	1	BRASS BAR	Ni PLATED
2	COVER	1	PB	UL-94V0(BLACK)
1	BODY	1	PBT	UL-94V0(BLACK)

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1:1

.XX±

DATE

.XXX±

ANG±

煜倫股份有限公司

www.morethanall.com

SIZE A4

PJECTION



ORDER INFORMATION

DCJ-RLT-xx-LF
SERIES | T | LEADFREE
20:2.0∅
25:2.5∅
TILTED
LOCK
DIP 90°

DESCRIPTION: DC POWER JACK