

$\phi 5.6 \pm 0.1$
 $\phi 6.5 \pm 0.1$

Specifications:

1. Electrical Test: ---250 volts AC max., at 2 Amps. Dielectric withstanding---500 volts AC. Insulation Resistance---500 megohms Termination Resistance---35 max. after enviromental testing.
2. Mechanical:
Cable-to-plug Tensile Strength-20 lbs [89N] min. Durability:200 mating cycles.
3. Material & Finish:
Housing Material:Polycarbonate (PC)
Contact Blade: 1)High strength copper alloy [JIS C5191R-H (PBR 2)]
2)Our electro-plation is based on 100 micro inches nickel underplated, and selective gold plate in contact area.
Gold, thickness is according to the customer's requirements.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±


.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION



ORDER INFORMATION

MPQ-AHUxxBK-08-LF

SERIES	ABS	H TYPE	U2	8P	LEADFREE
				BLACK	
				56:5.6mm OUTLET	
				65:6.5mm OUTLET	

DESCRIPTION: