



	A	Wire	B
	1	Red	1
	2	Red	2
	3	Black	3
	4	Black	4
	5	Blue	5
Twist	6	White	6
	7	Black	7
Twist	8	Blue	8
	9	White	9
	10	Black	10
Twist	11	Blue	11
	12	White	12
	13	Black	13
Twist	14	Blue	14
	15	White	15
	16	Black	16
Twist	17	Blue	17
	18	White	18
	19	Black	19

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL1571 #28 OD:0.8 Red	2PCS	E108485
2	WIRE:	UL1571 #28 OD:0.8 Black	7PCS	E108485
3	WIRE:	UL1571 #28 OD:0.8 Brown	5PCS	E108485
4	WIRE:	UL1571 #28 OD:0.8 White	5PCS	E108485
5	HOUSING:	FI-H-20	1PCS	E186792
6	TERMINAL:	FI-TG-28	19PCS	E186792
7	HOUSING:	DF14-H-20	1PCS	E186792
8	TERMINAL:	DF14-T-28	19PCS	E186792
9	NYLON BRAID:	:60*143mm Black	1PCS	
10	ACETATE CLOTH TAPE:	W : 20*L40mm	2PCS	
11	WATERPROOF LABEL:	AS DRAWING	1PCS	

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION



ORDER INFORMATION

DF14FI-202028TB1-F20C-LF

SERIES

TUBE

28 AWG  
20 TO 20 WAY

LEADFREE  
200mm  
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: CABLE ASS"Y