

J1		J2
P1	MARKING LINE	P1
P2	GRAY	P2
P3	GRAY	P3
	S	
P62	GRAY	P62
P63	GRAY	P63
P64	GRAY	P64
PIN ASSIGNMENT		

NOTE:

1. FLAT CABLE: UL2651 28AWG(7/0.127)"40C TINNED AND STRAND COPPER WIRE
P=1.27MM. INSULATOR: PVC, GRAY
2. CONNECTOR: 40P IDC SOCKET W/NOSE. CONTACT GOLD FLASH.
INSULATOR: BLACK.
3. ELECTRONIC TEST CONDITION:
 - 3.1 100% OPEN SHORT & MIS-WIRE TEST
 - 3.2 CONDUCTIVE RESISTANCE: 1/MAX
 - 3.3 INSULATION RESISTANCE: 1/MIN, DCSV

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT/mm SCALE 1:1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

F2X2-xxxx-Fxxx-LF

SERIES

LEADFREE

15C2:15.2 CM

FEMALE TO FEMALE

1010:10 TO 10PIN

DESCRIPTION: 2.54 IDC xxP/xxP W/0 SR