

RECOMMENDED P.C.B LAYOUT

NOTES:

- Housing: Thermoplastics,UL94V-0
- Contact: Copper Alloy
- Shell: Copper Alloy/Steel
- Voltage Current Rating:1.5 AMP. 30V AC
- Insulation Resistance:1000M Ω Min.
- Contact Resistance:30 M Ω Max.
- Dielectric Withstanding Voltage:500W AC
- Temperature Range:-35 $^{\circ}$ C to +85 $^{\circ}$ C
- Insulator color: Black/White
- Plastic material:PBT/LCP/Others
- Shell finish:Nickel plated/Tin-Lead plated
- Mechanical:
- Mating Force:3.5KG MAX
- Unmating Force:0.7 KG MIN.

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X. \pm 0.25
 .X \pm 0.20
 .XX \pm 0.15
 .XXX \pm 0.10
 ANG \pm

PPOJECTION



ORDER INFORMATION

USB-SWF39xx-4A-LF
 SERIES | LEADFREE
 FEMALE | BK:BLACK
 | WH:WHITE
 90°SMT OFFSET 3.9mm

DESCRIPTION: USB-AF 沉板 有邊 內彈 端子SMT