

No 膠心: Nylon 9T + 30% G.F., UL 94V-0, 黑色
 端子: C5191-H, 鈹厚 = 0.2±0.01mm
 2. 電鍍:
 端子: 對接區: 選鍍金
 焊接區: 1u"Min.金
 鍍底: 50u"Min.

Dimension Information:

Part No.	Dim.	Dim.A	Dim.B	Dim.C	Dim.D
BCC25-SV65R2P-04		17.7	13.7	10.00	9.15
BCC25-SV65R2P-05		20.2	16.2	12.50	11.65
BCC25-SV65R2P-06		22.7	18.7	15.00	14.15
BCC25-SV65R2P-07		25.2	21.2	17.50	16.65
BCC25-SV65R2P-08		27.7	23.7	20.00	19.15
BCC25-SV65R2P-09		30.2	26.2	22.50	21.65
* BCC25-SV65R2P-10		32.7	28.7	25.00	24.15

*為已生產之Pin數

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ± 0.20

UNIT / mm

SCALE 1 : 1

.XX ± 0.10


DATE

.XXX ±

ANG ±

SIZE A4

P PROJECTION



ORDER INFORMATION

BCC25-SV65R2P-xx-LF
 SERIES | | | | LEADFREE
 | | | | 04~10WAY
 FEMALE | | | | POST
 | | | | RIGHT KEY #2
 | | | | HIGH 6.55mm
 | | | | 180°SMT

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: Housing for 2.5mm Pitch Battery Conn. Female Type