

**Performance:**

Meets C5e EIA/TIA 568B Standard.

**Materials:**

Body : Fireproof ABS UL-94V0  
 Metallic Case : Metal  
 Jack : 8P8C 50 micro inches gold plated  
 PCB : FR-4 / UL-94V0

**Electrical Specifications:**

Insulation Resistance : 500M ohms (min.)  
 Contact Resistance : 20m ohms (max.)  
 Current Rating : 1.5 Amps .  
 DC Resistance : 0.1 ohms (max.)  
 Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

**Mechanical Specifications:**

Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT/ mm SCALE 1:1

DATE

SIZE A4

X. ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

P PROJECTION



**ORDER INFORMATION**

RJX2-FSC5EPN28FM-0808-LF  
 SERIES | PANEL | CAT.5E | 8P8C FULL METAL LONG 28.7mm | LEADFREE  
 FEMALE TO FEMALE 180°

DESCRIPTION: C5e INLINE COUPLER FTP 50u