

NOTES 1:

UL Standard :

- 1.Rating: 300V 10A
- 2.Insulation Withstands Voltage:
AC 1500 V at 1 minute
- 3.Using Temperature Range:
-40°C~+115°C
- 4.Suitable Electric Wire:AWG 28~14

IEC Standard:

1. Rate Impulse Voltage: 4000V
- 2.Insulation Resistance:
500M Ω or more at DC500V

ITEM	NAME OF PART	MATERIAL	NOTES
6	CLAMP	STEEL	
5	SOLDER PIN	COPPER ALLOY	Tin Plated
4	COVER2	PA	UL94-V0 GREY
3	COVER1	PA	UL94-V0 GREY
2	HOUSING2	PA	UL94-V0 GREY
1	HOUSING1	PA	UL94-V0 GREY

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XX ±


DATE

.XXX ±

ANG ±

SIZE A4

PPOJECTION



ORDER INFORMATION

TBY035-SWL-xx-LF

SERIES | | | LEADFREE
| | | 02~24WAY
| | | LOCK
| | | SCREW WIRE
| | | FEMALE

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com