

NOTE:

1. MATERIAL:
HOUSING: HIGH-TEMP, UL94V-0; COLOR: BLACK.
CONTACT: COPPER ALLOY.
2. FINISH:
CONTACT AREA: TIN(BRIGHT) PLATING 100 u" THICKNESS MIN.
SOLDERING AREA: TIN(BRIGHT) PLATING 100 u" THICKNESS MIN.;
UNDER PLATING: NICKEL PLATING 50 u" THICKNESS MIN.


POS.	DIMENSION			POS.	DIMENSION		
	A	B	C		A	B	C
4	3.75	6.30	8.40	20	23.75	26.30	28.40
5	5.00	7.55	9.65	21	25.00	27.55	29.65
6	6.25	8.80	10.90	22	26.25	28.80	30.90
7	7.50	10.05	12.15	23	27.50	30.05	32.15
8	8.75	11.30	13.40	24	28.75	31.30	33.40
9	10.00	12.55	14.65	25	30.00	32.55	34.65
10	11.25	13.80	15.90	26	31.25	33.80	35.90
11	12.50	15.05	17.15	27	32.50	35.05	37.15
12	13.75	16.30	18.40	28	33.75	36.30	38.40
13	15.00	17.55	19.65	29	35.00	37.55	39.65
14	16.25	18.80	20.90	30	36.25	38.80	40.90
15	17.50	20.05	22.15	31	37.50	40.05	42.15
16	18.75	21.30	23.40	32	38.75	41.30	43.40
17	20.00	22.55	24.65	33	40.00	42.55	44.65
18	21.25	23.80	25.90	34	41.25	43.80	45.90
19	22.50	25.05	27.15	35	42.50	45.05	47.15

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY	CY	X, ± 0.40
CHECKED BY	GENIUS	.X ± 0.30
UNIT / mm	SCALE 1 : 1	.XX ± 0.20
DATE		.XXX ± 0.10
		ANG ±



ORDER INFORMATION

FPB-DLAL-xx-LF
SERIES | | | | LEAD FREE
04~35WAY
DIP 180° | | | | L TYPE FOOT
SINGLE CONTACT
NON ZIF

煜倫股份有限公司

www.morethanall.com

SIZE A4 PPROJECTION

DESCRIPTION: FPC/FFC 1.25 PITCH NON ZIF TOP ENTRY SINGLE CONTACT