

RECOMMENDED P.C.B. LAYOUT  
TOLERANCE±0.05  
TOP VIEW

Position Dimension	10 Thru 100
A	0.40 X No. of Positions /1.5+2.4
B	0.40 X No. of Positions / +1.75
C	0.40 X No. of Positions /

**Material:**

Housing: High Temperature Plastic UL94V-0.  
Contacts: Phosphor Bronze.

**Electrical Characteristics:**

Current Rating: 0.3 AMP.  
Dielectric Withstanding Voltage: AC 100V For 1 minute  
Insulator Resistance: 100MΩ min. at DC100V.  
Contact Resistance: 90mΩ max. at AC 1mA.  
Operating Temperature: -25°C ~+85°C .

**\*RoHS Compliant**

100	23.10	20.95	19.60
90	21.10	18.95	17.60
80	19.10	16.95	15.60
72	17.50	15.35	14.00
70	17.10	14.95	13.60
60	15.10	12.95	11.60
50	13.10	10.95	9.60
40	11.10	8.95	7.60
34	9.90	7.75	6.40
30	9.10	6.95	5.60
26	8.30	6.15	4.80
24	7.90	5.75	4.40
22	7.50	5.35	4.00
20	7.10	4.95	3.60
16	6.30	4.15	2.80
14	5.90	3.75	2.40
12	5.50	3.35	2.00
10	5.10	2.95	1.60
Number of Position	A	B	C


**RoHS Compliant**

TOLERANCES ARE



DRAWING BY CY  
CHECKED BY GENIUS  
UNIT / mm SCALE 1 : 1  
DATE  
SIZE A4

X.±  
.X±  
.XX±  
.XXX±  
ANG±



**ORDER INFORMATION**

NP04-P03X-xxx-LF  
SERIES | LEADFREE  
| 010~100WAY  
| NON POST  
| UNMATED HIGH 0.3mm  
MALE

煜倫股份有限公司

www.morethanall.com

PJECTION

DESCRIPTION: