

Recommended PCB Layout

NOTES:

1. MATERIAL:

HOUSING: LCP, UL 94-V0, COLOR:BLACK
 CONTACT: COPPER ALLOY
 LEG: COPPER ALLOY

2. PLATING:

CONTACT: GOLD PLATED ON NICKEL OVERALL
 LEG: TIN PLATED ON NICKEL OVERALL

	A	B	C
10 PIN	4.70	2.00	3.20
12 PIN	5.20	2.50	3.70
14 PIN	5.70	3.00	4.20
20 PIN	7.20	4.50	5.70
22 PIN	7.70	5.00	6.20
24 PIN	8.20	5.50	6.70
30 PIN	9.70	7.00	8.20
32 PIN	10.20	7.50	8.70
36 PIN	11.20	8.50	9.70
40 PIN	12.20	9.50	10.70
50 PIN	14.70	12.00	13.20
60 PIN	17.20	14.50	15.70
80 PIN	22.20	19.50	20.70

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1


DATE

SIZE A4

TOLERANCES ARE

X ±
 .X ± 0.25
 .XX ± 0.20
 .XXX ±
 ANG ± 3°

PJECTION



ORDER INFORMATION

DF12-P23E-xxx-LF

SERIES | LEADFREE
 | 010-080 WAY
 | EAR
 | 2.3mm HIGH
 | MALE

DESCRIPTION: 0.5Ph Board to Board SMT Vertical 2.1H