


RECOMMENDED PC BOARD LAYOUT

板上型



## Technical Data

Material:

Contact material: PHOSPHOR BRONZE

Insulator material: Black polyester UL94V-0

Standard: LCP

Electrical:

Current rating: 1.0Amps/contact max

Contact resistance:  $\leq 20\text{m}\Omega$ /contact

Insulation resistance:  $\geq 1000\text{M}\Omega$  at  $V=100\text{V}$

Withstanding voltage: 300V AC/minute

Mechanical:

Operating temperature:

Tin plated:  $-40^{\circ}\text{C}$  to  $+105^{\circ}\text{C}$

Soldering temperature:  $+280^{\circ}\text{C}$ , 10s max

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PJECTION

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



ORDER INFORMATION

ESATA-PWB-07-LF

SERIES LEADFREE  
07 WAY  
BOTTOM CONTACT  
90°SMT  
MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: