

Material

- Item (a) Terminal (Body): Thermoplastic (UL94V-0)
- Item (b) Terminal (Lever): Thermoplastic (UL94V-0)
- Item (c) Spring clamp : Stainless Steel
- Item (d) Female Contact : PhBz(CuSn), Tin plated
- Item (e) Terminal (Cover): Thermoplastic (UL94V-0)

Electrical

- Voltage rating: 300VAC
- Current rating: 10A
- Solid wire(AWG): 14 ~ 26
- Stranded wire(AWG): 14 ~ 26
- Wire strip length: 7 ~ 8mm
- Withstanding Voltage: 1.6KV
- Size of the PCB: 1.6±0.2mm
- Operating temperature: -40°C to +115°C

Poles	2	3	4	5	6	7	8	9	10	11	12	13
Dim A	10	15	20	25	30	35	40	45	50	55	60	65
Dim B	11.4	16.4	21.4	26.4	31.4	36.4	41.4	46.4	51.4	56.4	61.4	66.4
TOL	±0.15						±0.20					
Poles	14	15	16	17	18	19	20	21	22	23	24	
Dim A	70	75	80	85	90	95	100	105	110	115	120	
Dim B	71.4	76.4	81.4	86.4	91.4	96.4	101.4	106.4	111.4	116.4	121.4	
TOL	±0.30						0.35					

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4


- X, ±
- .X ±
- .XX ±
- .XXX ±
- ANG ±

PJECTION



ORDER INFORMATION

TBY050-EW-xx-LF



DESCRIPTION:

煜倫股份有限公司

www.morethanall.com