

NOTES

1.MATERIAL

1.1 Insulator: P.B.T+15% G.F(UL94V-0)

1.2 Contact:Coppo alloy

Plating:Ni 30u" ~80u" Plated of all,Au Gold Flsh of all.

2.SPECIFICATION

2.1 Current Rating: 1 Amp

2.2 Current Voltage: 30V RMS Max

2.3 Dielectric Withstanding: AC 500V min Per minute

2.4 Insulation Resistance: 500M ohms min At

DC 500V

2.5 Contact Resistance: 20m ohms Max

2.6 Operating Temperature: -45°C ~ 105°C

2.7 Insertion force: 0.5Kgf/pin MAX.

2.8 Withdrawal force: 0.1Kgf/pin MIN.

*" 標示是重點管控尺寸

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

X, ±
.X ± 0.35
.XX ± 0.20
.XXX ± 0.10
ANG ± 2°

PPOJECTION



ORDER INFORMATION



煜倫股份有限公司

www.morethanall.com

DESCRIPTION: MJ 6A黑磷銅半面金 無毒