

Specifications

Contact Resistance : $\leq 30m$ max. at DC 100mA
 Insulator Resistance : $1000M$ min. at DC 500V
 Current Rating: 1 AMP
 Dielectric Withstanding
 Voltage: AC 500V For 1 minute
 Operating Temperature : $-55^{\circ}\sim+105^{\circ}c$
 Contact : MALE Brass
 FEMALE Phosphor Bronze
 Housing : PBT & 30% Glass Fiber (UL 94V-0)

Dimension

| Positon | A | B | C | D |
|---------|-------|-------|-------|-------|
| 9 | 16.92 | 24.99 | 31.16 | 10.16 |
| 15 | 25.50 | 33.32 | 39.42 | 17.78 |
| 25 | 38.96 | 47.04 | 53.34 | 30.48 |
| 37 | 55.45 | 63.50 | 69.68 | 45.72 |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PJECTION

X. \pm
 .X \pm
 .XX \pm
 .XXX \pm
 ANG \pm



ORDER INFORMATION

DFMS-PK-xx-LF

SERIES | LEADFREE
 | 09~37WAY
 | BLACK
 | MALE

DESCRIPTION: SUB I.D.C TYPE