

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL1007 #26 紅	1PCS	E108485
2	WIRE:	UL1007 #26 黑	1PCS	E108485
3	HOUSING:	PR-P-02	1PCS	E191023
4	TERMINAL:	PR-M-24	2PCS	
5				
6				
7				
8				
9				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1

.XX±


DATE

.XXX±

ANG±

SIZE A4

PPOJECTION



ORDER INFORMATION

PRX1-020026-M5C-LF

SERIES

LEADFREE

50mm

MALE

26 AWG

02 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: CABLE ASS"Y