


NOTE:
CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F.

- MATERIAL:
 - HOUSING: PA46, WITH GLASS FIBER, UL94V-0, STANDARD COLOR-BLACK.
 - INSERT HOUSING: PA46, WITH GLASS FIBER, UL94V-0, STANDARD COLOR-BLACK.
 - CONTACTS: PHOSPHOR BRONZE.
 - SHELL: BRASS.
- FINISH:
 - CONTACTS: 0.152µm [6µ"] GOLD PLATED ON CONTACT AREA, GOLD FLASH PLATED ON SOLDER TAIL, WITH ENTIRE CONTACT UNDERPLATED 1.27µm [50µ"] MIN. NICKEL
 - SHELL: 0.508µm [20µ"] MIN. NICKEL PLATED.



RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm

SCALE 1:1

DATE

SIZE A4

PJECTION

X, ±
.X ± 0.25
.XX ± 0.13
.XXX ± 0.05
ANG ±

ORDER INFORMATION

MJF13U-KX06B3-0808-LF

SERIES | | | | LEADFREE
| | | | 8P8C
| | | | REAR TAB 3.43mm
| | | | 06u" GOLD
| | | | NON EAR
| | | | BLACK

DESCRIPTION: MODULAR JACK CONNECTOR RJ45, WITHOUT LED, WITH SHELL, DIP TYPE