

Recommended P.C.B Layout

**MATERIAL**

Contact Pin : Brass

Insulator : PBT UL94-V0

**SPECIFICATION**

Current Rate : 3 AMP

Insulation Resistance : 5000MΩMin. at DC 500V

Contact Resistance : 20mΩMax. at DC 100mA

Dielectric Voltage : AC 500V for one minute

Operation Temperature : -40°C to + 105°C

POLES	DIM E	POLES	DIM E
		21	50.80
2	2.54	22	53.34
3	5.08	23	55.88
4	7.62	24	58.42
5	10.16	25	60.96
6	12.70	26	63.50
7	15.24	27	66.04
8	17.78	28	68.58
9	20.32	29	71.12
10	22.86	30	73.66
11	25.40	31	76.20
12	27.94	32	78.74
13	30.48	33	81.28
14	33.02	34	83.82
15	35.56	35	86.36
16	38.10	36	88.90
17	40.64	37	91.44
18	43.18	38	93.98
19	45.72	39	96.52
20	48.26	40	99.06

**RoHS Compliant**

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm


SCALE 1:1

DATE

SIZE A4

P PROJECTION

X. ±  
X ± 0.30  
.XX ± 0.20  
.XXX ±  
ANG ±



**ORDER INFORMATION**

H-D-3Xxx-LF  
SERIES | LEADFREE  
3X02:06WAY  
3X40:120WAY  
DIP 180°

DESCRIPTION: PIN HEADER 2.54\*2.54mm STRAIGHT TYPE, TRIPLE ROWS