



△ RECOMMEND PANEL CUT-OUT

- NOTE**
- MATERIAL :**
    - 1-1. HOUSING : PBT UL94V-0 ; COLOR : BLACK
    - 1-2. CONTACT : BRASS
    - 1-3. SHELL : BRASS
    - 1-4. NUT : BRASS
    - 1-5. O-RING : NBR ; COLOR : BLACK
  - FINISH :**
    - 2-1. CONTACT : 10 MICRO INCHES MIN. GOLD PLATED  
UNDER PLATE : NICKEL
    - 2-2. SHELL : NICKEL PLATED 60u" ~ 100u" OVER ALL
    - 2-3. NUT : NICKEL PLATED 60u" ~ 100u" OVER ALL
  - ELECTRICAL SPECIFICATION :**
    - 3-1. Rated current : 4A
    - 3-2. Rated Voltage : 250V
    - 3-3. Water proof : IPX7
  - Environmental :**
    - 4-1. Operation Temperature : -40°C~85°C

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES  
**煜倫股份有限公司**

DRAWING BY CY  
CHECKED BY GENIUS  
UNIT / mm SCALE 1 : 1  
DATE

X, ±  
.X ± 0.10  
.XX ± 0.05  
.XXX ± 0.03  
ANG ± 1°



**ORDER INFORMATION**

M12-PSPANO-04-LF  
SERIES | T | T | T | T | LEADFREE  
RING | 04WAY  
MALE | NUT | PANEL FRONT  
SOLDER

www.morethanall.com

SIZE A4 PROJECTION

DESCRIPTION: WP M12 4PIN(M) 4PIN(F) (PG9)A code