



PCB LAYOUT

NOTES:

- Housing: Thermoplastics,UL94V-0
- Contact: Copper Alloy
- Shell: Copper Alloy/Steel
- Voltage Current Rating:1.5 AMP. 30V AC
- Insulation Resistance:1000MΩ Min.
- Contact Resistance:30 MΩ Max.
- Dielectric Withstanding Voltage:500W AC
- Temperature Range:-35°C to +85°C
- Insulator color: Black
- Plastic material:PBT/LCP/Others
- Shell finish:Nickel plated/Tin-Lead plated
- Mechanical:
- Mating Force:3.5KG MAX
- Unmating Force:0.7 KG MIN.

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.25  
 .X ± 0.20  
 .XX ± 0.15  
 .XXX ± 0.10  
 ANG ±

PJECTION



ORDER INFORMATION

USB-SRZ1BK-4A-LF  
 SERIES | CLIP | BLACK | LEADFREE  
 | | DIP 90° | 4 PIN A TYPE  
 | | FEMALE

DESCRIPTION: