



備註 /NOTE:

1. 安規 /SAFETY:

- 1-1. 規格 /RATING: 100V AC MAX or 12V DC 2A MAX
- 1-2. 絕緣阻抗 /INSULATION RESISTANCE: 50M ohm MIN at 250V DC
- 1-3. 絕緣耐壓 /WITHSTANDING: 250V AC at 1 MINUTE

2. 材質 /MATERIAL:

- 2-1. 外套 /PLASTIC COVER:ABS
- 2-2. 銅管 /SHELL: 黃銅 /BRASS
- 2-3. 上蓋 /CAP: 黃銅 /BRASS
- 2-4. 線扣 /CABLE FIXER: 黃銅 /BRASS
- 2-5. 膠芯 /HOUSING:PBT
- 2-6. 針 /PIN: 黃銅 /BRASS
- 2-7. 塑鋼雙腳 /POM RING:POM
- 2-8. 彈簧 /SPRING: 鋼 /STEEL
- 2-9. 中筒 /PLASIC TUBE:ABS
- 2-10. SR:PVC

3. 電鍍 /PLATING:

- 3-1. 銅管 /SHELL: 鍍 /NICKEL
- 3-2. 上蓋 /CAP: 鍍 /NICKEL
- 3-3. 線扣 /CABLE FIXER: 鍍 /TIN
- 3-4. 針 /PIN: 銀 /SILVER

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm

SCALE 1:1

DATE

SIZE A4

PJECTION

X, ±  
.X ± 0.10  
.XX ± 0.05  
.XXX ±  
ANG ±



ORDER INFORMATION

MDP-PA2B1-03-LF  
SERIES | | LEADFREE  
| | 03WAY  
| SINGLE PACKING  
ASSEMBLY  
MALE

DESCRIPTION: POWER 3P 公座 成品 系列 (雙箭頭)