

| Circuits | Dimension | |
|----------|-----------|-------|
| | A | B |
| 6 | 2.54 | 10.11 |
| 8 | 3.81 | 11.38 |
| 10 | 5.08 | 12.65 |
| 12 | 6.35 | 13.92 |
| 14 | 7.62 | 15.19 |
| 16 | 8.89 | 16.46 |
| 20 | 11.43 | 19.00 |
| 24 | 13.97 | 21.54 |
| 26 | 15.24 | 22.81 |
| 30 | 17.78 | 25.35 |
| 34 | 20.32 | 27.89 |
| 40 | 24.13 | 31.70 |
| 44 | 26.67 | 34.24 |
| 50 | 30.48 | 38.05 |
| 60 | 36.83 | 44.40 |
| 64 | 39.37 | 46.94 |
| 68 | 41.91 | 49.48 |
| 80 | 49.53 | 57.10 |
| 100 | 62.23 | 68.90 |

Conteract:
 Contact:Brass.
 Insuiator:LCP.
 Finish:Gold flash plated over nickel.

P.C.Board Layout

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PPOJECTION



ORDER INFORMATION

HAB-VC-xxx-LF
 SERIES | LEADFREE
 | 006-100WAY
 CAP
 180° SMT

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com