

WIRING CHART

A	COLOR	B
1	Red	1
2	Black	2
3	Brown	3
4	Orange	4
5	Green	5

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL1571 #28 OD:0.8 Red	1PCS	E108485
2	WIRE:	UL1571 #28 OD:0.8 Black	1PCS	E108485
3	WIRE:	UL1571 #28 OD:0.8 Brown	1PCS	E108485
4	WIRE:	UL1571 #28 OD:0.8 Orange	1PCS	E108485
5	WIRE:	UL1571 #28 OD:0.8 Green	1PCS	E108485
6	HOUSING:	PNM-H-05	2PCS	E191023.
7	TERMINAL:	PNM-TG-28	10PCS	
8	H. S TUBE:	3.5φ*210mm Black F32	1PCS	E203950
9	LABEL			

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

P PROJECTION



ORDER INFORMATION

PNMX2-050528HT1-F26C-LF

SERIES

LEADFREE  
260mm  
FEMALE TO FEMALE  
HEAT SHRINK TUBING  
28 AWG  
05 TO 05 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: CABLE ASS"Y