

NOTE:

1.MATERIAL :

UL94V-0, COLOR : BLACK
 HOUSING : High Temperature Thermoplastic ,
 TERMINAL(max): Copper Alloy,THICKNESS = 0.30 mm
 TERMINAL(min): Copper Alloy,THICKNESS = 0.25 mm
 FORKLOCK: Copper Alloy,THICKNESS = 0.30 mm

2.PLATING:

CONTACT:GOLD OVER 50u" MIN NICKEL UNDERPLATE(SEE TABLE)
 SOLDER TAIL: 150u"MIN MISTY TIN 50u" MIN NICKEL UNDERPLATE
 GOLD SPECIFICATION:SEE TABLE

3.ELECTRONICAL SPECIFICATION:

CURRENT RATING: 1.5 AMPERE PER CONTACT
 CONTACT RESISTANCE: 30 MILLIOHMS MAX.
 INSULATION RESISTANCE: 1000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC.
 OPERATING TEMPERATURE: -20°C~+85°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.20
 .XX ± 0.15
 .XXX ±
 ANG ± 3°

PJECTION



ORDER INFORMATION

SAS-SVP-29-LF
 SERIES | | | LEADFREE
 | | | 29 WAY
 | | | POST
 | | | 180° SMT
 | | | FEMALE

DESCRIPTION: SAS 29P 母頭 SMT柱子大小型

煜倫股份有限公司

www.morethanall.com