





■ Specifications :

- Voltage rating: 300V AC / DC
- Current rating: 3A AC / DC
- Withstanding voltage: 1700V AC/minute
- Temperature range: -55°C~+105°C
- Insulation resistance: ≥1000MΩ
- Contact resistance: ≤20mΩ
- After environmental testing: ≤40mΩ



LEB-SWX-02	LCP UL 94V-0	Phosphor Bronze	Tin-Plated	Brass	Tin-Plated
PART NO	Material	Material(Pin)	Finish(Pin)	Material (Solder Tab)	Finish (Solder Tab)

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1

.XX ± 0.20


DATE

.XXX ± 0.10

ANG ±

SIZE A4

PJECTION



ORDER INFORMATION

LEB-SWX-02-LF
SERIES | | | LEADFREE
| | | 02 WAY
| | | NON POST
| | | 90°SMT
| | | FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 4.00mm BTB Style Connectors