

THICKNESS	C
0.8t-1.0t	19.8
1.0t-1.2t	19.9
1.2t-1.5t	19.9
2t	20.0
3.5t	20.1

**SPECIFICATION:**

1. INSULATION RESISTANCE: OVER 100MΩ 500V DC.
2. DIELECTRIC STRENGTH: 2000V AC ONE MINUTE.
3. Body Material: Black Glass-Fiber Thermoplastic . UL 94V-2~0
4. Contact Terminal Material: C2680 Sn plated thickness 3~5um

Rating:AC 15A 250V	
Mark	Safety Regulation
RU	UL
cRU	CUL
Rating:AC 10A 250V	
Mark	Safety Regulation
	VDE
	CCC
	ENEC

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ± 0.10  
ANG ±

PJECTION



ORDER INFORMATION

ACF-PQ4PA-03-LF

SERIES | LEADFREE  
03 WAY  
PANEL FRONT  
4.8mm TAB  
MALE

DESCRIPTION: