

PIN數	A	B	C
36	7.65	6.00	25.00
64	21.65	20.00	39.00
98	38.65	37.00	56.00
164	71.65	70.00	89.00

Note:

- Electrical Performance
  - Dielectric Withstanding Voltage: 500V/AC For 1.0 Minute.
  - Contact Resistance: 30m
  - Insulation Resistance: 1000M
  - Current Rating: 1.1A
- Mechanical Performance.
  - CONTACT INSERTION FORCE: 0.115Kg Max Per.Contact Pair.
  - CONTACT WITHDRAWAL FORCE: 0.015Kg Min Per.Contact Pair.
  - Terminal Retention Force (in housing): 0.5Kg Minper Terminal.
- Material & Finish:
  - Insulator: Hi-Temp NY-9T UL 94V-0, 260°/10Sec, Black
  - Contact: BRASS
  - Plating: Tin Plating At Solder Tail Area; Gold Plating At Mating Area, All Over Nickel Plating.
- Environmental: Operating Temperature: -55 C~+105C

PCB LAYOUT

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES  
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X, ±  
.X ± 0.20  
.XX ± 0.10  
.XXX ± 0.001  
ANG ± 3°



ORDER INFORMATION

PCIX-VPEC-xxx-LF  
SERIES | | | | LEADFREE  
| | | | 036~164WAY  
| | | |  
| | | | CAP  
| | | | EAR  
| | | | POST  
| | | | 180°SMT

DESCRIPTION: PCI PH:1.0 SMT 成品

www.morethanall.com