

Specification:

Contact Resistance: 30m Ohm Max.
 Insulation Resistance: 100M Ohm Min.AT 500V DC
 Rated Voltage And Current: DC12V.2A Max;AC 100V.1A Max
 Dielectric Withstanding Voltage:250V AC For 1 Minute
 Durability (Life Test): 100 Cycles
 Insertion Force:4.0KG Maximum.
 Extraction Force:0.9KG Minimum.

NO.	NAME	MATERIAL	FINISH	Q'TY	REMARK
1	HOUSING	PBT G.F.	BLACK	1	
2	CONTACT TERM.	PHOS. BRONZE T:0.2	GOLD-TIN PLATED	8	Gold:1~3u"; NI:40~60u"; TIN:120u" (100% pure Tin of lead free plating)
3	GROUND TERM.	BRASS T:0.4	TIN PLATED	1	TIN:120~200u"
4	BOTTOM COVER	PBT G.F.	BLACK	1	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.38
 .X ± 0.25
 .XX ± 0.13
 .XXX ± 0.05
 ANG ±

PPOJECTION



ORDER INFORMATION

MDJ-S-08-LF
 SERIES | LEADFREE
 08 WAY
 ALL PLASTIC

DESCRIPTION: MINI DIN JACK FLAT 8 PIN DIP