

PCB Layout

MATERIALS ELECTRICAL                      cULus                      CQC  
 RATED VOLTAGE & CURRENT:            250 V, 10 A            /            250 V, 10 A  
 WITHSTAND VOLTAGE:                      AC 2000 V/Min        /            AC 2000 V/Min  
 INSULATION RESISTANCE:                1000 MΩ OR MORE AT DC 500 V  
 OPERATING TEMPERATURE RANG:        -40 °C ~ +115 °C  
 SCREW TORQUE VALUE:                    5.3 Lb-In.              /            0.8 Nm  
 WIRE RANGE:                                22 - 18 AWG            /            22 - 18 AWG  
 1) MOLDED PARTS:                        Thermoplastic, UL 94 V-0 BLACK  
 2) TERMINAL:                                BRASS, 0.8t, Tin PLATED  
 3) TERMINAL SCREWS:                    STEEL, Ni PLATED, M3

△ APPROVAL:  

POLE	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
A		13.70	20.05	26.40	32.75	39.10	45.45	51.80	58.15	64.50	70.85	77.20	83.55	89.90	96.25	102.60
B		6.35	12.70	19.05	25.40	31.75	38.10	44.45	50.80	57.15	63.50	69.85	76.20	82.55	88.90	95.26
POLE	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
A	108.95	115.30	121.65	128.00	134.35	140.70	147.05	153.40	159.75	166.10	172.45	178.80	185.15	191.50	197.85	
B	101.60	107.95	114.30	120.65	127.00	133.35	139.70	146.05	152.40	158.75	165.10	171.45	177.80	184.15	191.00	

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

P PROJECTION 

X. ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±



ORDER INFORMATION

TBC063-D-xx-LF

SERIES

LEADFREE

02-31WAY

DIP 180°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: