



A	COLOR	B
1	RED	1
2	BLACK	2

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY
1	WIRE:	UL2468 #24*2F (RED, BLACK) OD: 1.8*1.8	1pcs
2	CONN:	DC PLUG $\phi 5.5 \times \phi 2.1 \times L: 20.5$	1pcs
3	OUTERMOLED:	PVC 45P BLACK GH-044	3.5g
4	HOUSING:	MK-H-02	1pcs
5	TERMINAL:	MK-T-22	2pcs

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

DCMK-200224C1-E10N-LF

SERIES

LEADFREE
254mm
MALE TO FEMALE
COMBO WIRE
24 AWG
DC 2.0Ø TO MK 02 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: CABLE ASS'Y