


Technical drawing of the front view of a printed circuit board (PCB) for a 16-bit parallel adder. The drawing shows a rectangular board with various components and dimensions. Key features include a 16-pin DIP package at the top center, a 16-pin DIP package at the bottom center, and a 16-pin DIP package at the bottom left. Dimensions are given in millimeters with tolerances. A coordinate system is shown with X and Y axes. A table of dimensions is provided below the drawing.

Dimension	Value
1	13.00 ± 0.05
2	1.90 ± 0.05
3	7.62 ± 0.05
4	6.15
5	2.00 ± 0.05
6	9.87 ± 0.05
7	8.20 ± 0.05
8	2.00 ± 0.05
9	10.20 ± 0.05
10	2.00 ± 0.05
11	11.88 ± 0.05
12	2.00 ± 0.05
13	3.30 ± 0.05
14	2.70 ± 0.05
15	19.10 ± 0.05
16	0.40
17	9.55
18	19.90
19	0.40
20	11.88 ± 0.05
21	2.00 ± 0.05
22	3.30 ± 0.05
23	2.70 ± 0.05
24	19.10 ± 0.05
25	0.40
26	9.55
27	19.90
28	0.40
29	11.88 ± 0.05
30	2.00 ± 0.05
31	3.30 ± 0.05
32	2.70 ± 0.05
33	19.10 ± 0.05
34	0.40
35	9.55
36	19.90
37	0.40
38	11.88 ± 0.05
39	2.00 ± 0.05
40	3.30 ± 0.05
41	2.70 ± 0.05
42	19.10 ± 0.05
43	0.40
44	9.55
45	19.90
46	0.40
47	11.88 ± 0.05
48	2.00 ± 0.05
49	3.30 ± 0.05
50	2.70 ± 0.05
51	19.10 ± 0.05
52	0.40
53	9.55
54	19.90
55	0.40
56	11.88 ± 0.05
57	2.00 ± 0.05
58	3.30 ± 0.05
59	2.70 ± 0.05
60	19.10 ± 0.05
61	0.40
62	9.55
63	19.90
64	0.40
65	11.88 ± 0.05
66	2.00 ± 0.05
67	3.30 ± 0.05
68	2.70 ± 0.05
69	19.10 ± 0.05
70	0.40
71	9.55
72	19.90
73	0.40
74	11.88 ± 0.05
75	2.00 ± 0.05
76	3.30 ± 0.05
77	2.70 ± 0.05
78	19.10 ± 0.05
79	0.40
80	9.55
81	19.90
82	0.40
83	11.88 ± 0.05
84	2.00 ± 0.05
85	3.30 ± 0.05
86	2.70 ± 0.05
87	19.10 ± 0.05
88	0.40
89	9.55
90	19.90
91	0.40
92	11.88 ± 0.05
93	2.00 ± 0.05
94	3.30 ± 0.05
95	2.70 ± 0.05
96	19.10 ± 0.05
97	0.40
98	9.55
99	19.90
100	0.40
101	11.88 ± 0.05
102	2.00 ± 0.05
103	3.30 ± 0.05
104	2.70 ± 0.05
105	19.10 ± 0.05
106	0.40
107	9.55
108	19.90
109	0.40
110	11.88 ± 0.05
111	2.00 ± 0.05
112	3.30 ± 0.05
113	2.70 ± 0.05
114	19.10 ± 0.05
115	0.40
116	9.55
117	19.90
118	0.40
119	11.88 ± 0.05
120	2.00 ± 0.05
121	3.30 ± 0.05
122	2.70 ± 0.05
123	19.10 ± 0.05
124	0.40
125	9.55
126	19.90
127	0.40
128	11.88 ± 0.05
129	2.00 ± 0.05
130	3.30 ± 0.05
131	2.70 ± 0.05
132	19.10 ± 0.05

P.C.B layout

RoHS Compliant

TOLERANCES ARE



MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

 $X_{\pm}$

CHECKED BY GENIUS

 χ^2

UNIT / mm

SCALE 1:1

 $\cdot XXX \pm$

DATE _____

PPOJECTION

ORDER INFORMATION

MSDC-W19PA-11-LF

SERIES

S T T T T T
LEADFREE
11 WAY
UPPER CONTACT
PUSH PUSH
POST 19.90mm
90°SMT

DESCRIPTION: