

Specification
 1.Current Rating:0.5A AC/DC
 2.Voltage Rating:30V AC/DC
 3.Contact Resistance:20mΩ Max.
 4.Insulation Resistance:100MΩ Min.
 5.Withstand Voltage:AC200V/Minute
 6.Operating Temperature:-25°C~+85°C
 Material:
 1.Housing:Thermoplastic UL94V-0
 2.Contact Pin:Copper Alloy T=0.15
 3.Tab:Copper Alloy T=0.2
 Finish:
 1.Housing:Natural
 2.Contact Pin:Gold Plated
 3.Tab:Gold Plated

RECOMMENDED P.C.B LAYOUT

PIN	DIM.A	DIM.B	DIM.C	DIM.D	PIN	DIM.A	DIM.B	DIM.C	DIM.D
02	0.80	1.90	3.78	3.04	06	4.00	5.10	6.98	6.24
03	1.60	2.70	4.58	3.84	07	4.80	5.90	7.78	7.04
04	2.40	3.50	5.38	4.64	08	5.60	6.70	8.58	7.84
05	3.20	4.30	6.18	5.44					

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY


CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PROJECTION

X ±
 .X ± 0.35
 .XX ± 0.25
 .XXX ± 0.15
 ANG ±



ORDER INFORMATION

SUR-VC-xx-LF
 SERIES | LEADFREE
 | 02-08 WAY
 CAP
 180°SMT

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: