


DIP TYPE



■ MATERIAL

INSULATOR: PBT GLASS FIBER (UL94V-0).
CONTACT: BRASS
PLATING: GOLD OVER NICKEL.

■ SPECIFICATION

CURRENT RATING: 3 AMP.
INSULATION RESISTANCE: 5000 MEGOHMS MIN AT 500 VDC.
CONTACT RESISTANCE: 20 MILLIOHMS MAX.
VOLTAGE : 500V FOR ONE MINUTE.

■ ENVIRONMENTAL

TEMPERATURE RANGE: -40°C TO +125°C.

UNLESS OTHERWISE SPECIFIED	
0-10 ±0.2	10-30 ±0.3
30-100 ±0.4	100-300 ±0.5
OVER 300 ±0.6	ANGULAR ±0.5°

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±


.X ±

.XX ±

.XXX ±

ANG ±

P PROJECTION



ORDER INFORMATION

KE-DXE5BK-20M13-LF
SERIES | BLACK | 20 WAY MOLDED KEY #1#3 | LEADFREE
NON EAR | ROW PITCH 5.08mm | DIP 180°

DESCRIPTION: 3.96 PITCH WITH OUT MOUNTING EAR