

WIRING CHART

A	COLOR	B	A	COLOR	B
3	BLACK	28	16	BLACK	15
4	BLACK	27	17	BLUE	14
5	BLUE	26	18	WHITE	13
6	WHITE	25	19	BLACK	12
7	BLACK	24	20	BLACK	11
8	BLUE	23	21	RED	10
9	WHITE	22	22	RED	5
10	BLACK	21	24	RED	6
11	BLUE	20	27	RED	3
12	WHITE	19	28	RED	2
13	BLACK	18			
14	BLUE	17			
15	WHITE	16			

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL1571 #28 OD:0.6 RED	5PCS	E108485
2	WIRE:	UL1571 #28 OD:0.6 BLACK	8PCS	E108485
3	WIRE:	UL1571 #28 OD:0.6 BLUE	5PCS	E108485
4	WIRE:	UL1571 #28 OD:0.6 WHITE	5PCS	E108485
5	HOUSING:	FIX-HL-30	2PCS	E186792
6	TERMINAL:	FIX-TG-28	46PCS	
7	Acetate Cloth Tape	W:30*L:90	1PCS	
8				
9				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1:1

.XX±


DATE

.XXX±

ANG±

SIZE A4

PJECTION



ORDER INFORMATION

FIXX2-302328LLTB1-M15C-LF

SERIES

LEADFREE

150mm

MALE TO MALE

ACETATE CLOTH TAPE

30P/23C

LATCH

28 AWG

DESCRIPTION: CABLE ASS'Y

煜倫股份有限公司

www.morethanall.com