

- NOTE:
- SAFETY:
 - RATING: 0.5A/250Vac.
 - CONTACT RESISTANCE: 30mOhm MAX.
 - INSULATION RESISTANCE: 100Mohm MIN.
 - DIELECTRIC WITHSTANDING VOLTAGE: 100Vac/1minute.
 - DURABILITY: 10,000cycles.
 - MATERIAL:
 - PIN:PHOSPHOR BRONZE.
 - HOUSING:NYLON COLOR:TABLE A $\Delta\Delta$
 - LATCH:STAINLESS #304.
 - SHELL:STAINESS #304. Δ
 - COVER:NYLON 66 COLOR:BLACK. Δ
 - PLATING:
 - PIN:GOLD 15u" MIN ON CONTACT AREA, TIN 100u" MIN ON SOLDER TAILS, UNDERPLATED NICKEL OVER ALL 60u" MIN.

TABLE A

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT/mm SCALE 1:1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

MISB-PAxx-5B-LF
SERIES | MALE | LEADFREE
5 PIN B TYPE
BK:BLACK
WH:WHITE
ASSEMBLY

DESCRIPTION: MICRO USB 5PIN(M) B TYPE