

T:1.6 Dimensions of PC board holes
Tolerance : ±0.1(Printed-top view)

SCHEMATIC				
PJ-R35-05C	PJ-R35-04R	PJ-R35-04L	PJ-R35-03	PJ-R35-03B

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

8	COVER	1	PBT 4815	UL-94V0
7	HOUSING	1	PBT 4815	UL-94V0
6	AXIS SUPPORT	1	C2680	MB:Cu Ni PLATED
5	5# CONTACT FOOT	1	C5191	MB:Cu Sn PLATED
4	4# CONTACT FOOT	1	C2680	MB:Cu Sn PLATED
3	3# CONTACT FOOT	1	C2680	MB:Cu Sn PLATED
2	2# CONTACT FOOT	1	C5191	MB:Cu Sn PLATED
1	1# CONTACT FOOT	1	C2680	MB:Cu Sn PLATED
LTR	PART NAME	QTY	MATERIAL	REMARK

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

PJ-R35-xxx-LF
SERIES | LEADFREE SCHEMATIC
3.0+5.0mm
DIP 90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: MINIATURE JACK