

A	COLOR	B
1	RED	1
2	GRAY	2
3	GRAY	3
4	GRAY	4
5	GRAY	5
6	GRAY	6
7	GRAY	7
8	GRAY	8
9	GRAY	9
10	GRAY	10

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5Ω Max
3. INSULATION RESISTANCE: 20MΩ Min

NO.	ITEM.	DESCRIPTION	P/N.	SUPPLIER	Q'TY
1	WIRE:	UL 2651 #28 10P FLAT CABLE PH:1.27		MORETHANALL	1PCS
2	IDC:	10P W/NOSE PH:2.54 BLACK (2 Piece type)	F-C2-10-LF	MORETHANALL	2SET
3					
4					
5					
6					

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION



ORDER INFORMATION

F2X2-1010-F15C2-LF

SERIES

LEADFREE

152mm

FEMALE TO FEMALE

10 TO 10 PIN

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: CABLE ASS'Y