



Pos.	Dim.A	Dim.B	Dim.C	Dim.D	Dim.E
6	12.32	6.35	5.08	12.12	1.9
8	14.86	8.89	7.62	14.66	1.9
10	17.40	11.43	10.16	17.20	3.8
12	19.94	13.97	12.70	19.74	3.8
14	22.48	16.51	15.24	22.28	3.8
16	25.02	19.05	17.78	24.82	3.8
18	27.56	21.59	20.32	27.36	3.8
20	30.10	24.13	22.86	29.90	3.8
24	35.18	29.21	27.94	34.98	3.8
26	37.72	31.75	30.48	37.52	3.8
30	42.80	36.83	35.56	42.60	3.8
34	47.88	41.91	40.64	47.68	3.8
40	55.50	49.53	48.26	55.30	3.8
44	60.58	54.61	53.34	60.38	3.8
50	68.20	62.23	60.96	68.00	3.8
60	80.90	74.93	73.66	80.70	3.8
64	85.98	80.01	78.74	85.78	3.8

備注:

- 1.加反折為3件式，不加反折為2件式。
- 2.加括號尺寸為參考尺寸。
- 3.未標示公差之尺寸參考公差表。
- 4.6PIN有鼻膠芯G處兩邊都無凹槽，無鼻膠芯G處只有一邊有凹槽；  
8/10/12PIN G處只有一邊有凹槽，14及14PIN以上G處兩邊都有凹槽。
- 5.A規格：6PIN有鼻膠芯G處只有一邊有凹槽。

\*Material:

Insulator: PBT+Glass Fiber (UL94V-0).

Contact: Copper Alloy.

Contact Plated: Gold or Tin over Nickel Plated.

All material accord with ROHS。

\*Specification:

Withstanding Voltage: AC 500V for 1 Minute.

Insulation Resistance: 100 M $\Omega$  Min. at DC 500V.

Contact Resistance: 1  $\Omega$  Max..

Operating Temperature: -40°C --- +105°C.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES  
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X.  $\pm$  0.30

.X  $\pm$  0.20

.XX  $\pm$  0.10

.XXX  $\pm$  0.05

ANG  $\pm$

PJECTION



ORDER INFORMATION

F-C3Y-xx-LF  
SERIES | LEADFREE  
| 06-64WAY  
| Y TERMINAL  
THREE TYPE

DESCRIPTION:

www.morethanall.com