

℄ P.C.B. EDGE

RECOMMENDED P.C.B. LAYOUT

SPECIFICATIONS

ELECTRICAL CHARACTERISTICS:

Contact Current Rating:3 Amperes.
 Dielectric Withstanding Voltage: AC 1000/60sec.r.m.s.
 Insulation Resistance:500 Medohms Minimum.at DC 500V.
 Contact Resistance:25 Milliohms Maximum.
 Operating Temperature:-55°C to+105°C.

MECHANICAL CHARACTERISTICS:

Contact Insertion Force:341 g.Maximum.
 Contact Separation Force:21 g.Minimum.
 Grounding Screw Torque:3 Kg.Minimum.

MATERIALS:

Contacts:Brass.
 Insulator: PBT UL 94V-0 Rated.
 Shell:Cold Roller Steel.
 Grounding Screw Torque:Brass

FINISHES:

Contact:Gold Flash.
 Shell:Nickel Plated.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X. ±
 .X ± 0.20
 .XX ± 0.10
 .XXX ±
 ANG ±

PPOJECTION



ORDER INFORMATION

HDCD135-SSZ-15-LF

SERIES | | | LEADFREE
 15 WAY
 CLIP
 SEMI GOLD
 FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: